

APPARATUS AND METHOD FOR ERROR ISOLATION IN HYBRID COMMUNICATIONS SYSTEMS

FIELD OF THE INVENTION

The invention relates to the isolation of errors in communications systems and, more particularly, to the isolation of errors in hybrid systems which include both packet switching and time division multiplexing elements.

BACKGROUND OF THE INVENTION

In 1876, inside a third floor walk-up garret apartment in the Scollay Square section of Boston Massachusetts, Alexander Graham Bell spoke the first sentence transmitted over telephone wires. Technical innovations have dramatically transformed the telecommunications industry over the past one hundred and twenty three years. For example, telecommunications switching systems have evolved considerably from "hand operated" systems in which one instrument was electrically connected (through a hierarchical switching network) to another through the intervention of a human operator who would physically plug one circuit into another. Such direct electrical connection of two or more channels between two points (at least one channel in each direction), a connection that provides a user with exclusive use of the channels to exchange information, is referred to as circuit switching, or line switching. Human operators have largely been replaced by systems which employ electronic switching systems (ESS, e.g., 5ESS), in which the instruments are automatically connected through the network by electronic systems. Nevertheless, such switching systems often still employ circuit switching, a technique which yields highly reliable service, particularly for such "real time" communications applications as voice, in which the momentary loss of a channel is annoying and repeated such losses are unacceptable. Electronic switching systems, such as the 5ESS may interconnect telephone instruments through circuit switching, employing

A hybrid switching device, such as an "extended" 5ESS may include both a circuit switching side, in the form of it's switching core, and a packet switching side, in the form of a multi-service module (MSM, also known as Packet Driver). Such a switching device may be connected to other switching devices through cables containing numerous shared telephone circuits, the cables often being referred to as trunks or paths. In order to locate faults within a packet switching section of a hybrid switch, or along a length of a trunk or a path associated with the packet switching section of the switch, a loopback test may be performed to test various portions, of the path between circuit switched components and packet switched components. In this way, the failed section may be located and adjustments may be made to correct the failure.

However, there is no facility currently available for a circuit switched side to initiate a loopback test that includes any portion of the packet switched side of the switch, or, conversely, for a packet switched side of the switched to initiate a loopback test that extends to any portion of the circuit switched side of the switch. Because such facilities are not available, a circuit switched side may route a call to a failed area of the packet switched side. Consequently, the call could be dropped by the packet switching side. Similarly, a call originating on the packet switching side may be dropped by a failed component on the circuit switching side of the switch and, without a means for locating errors on the circuit switching side, the packet switching side may continue, obviously, to send calls to a failed segment of the circuit side of the switch.

An apparatus and method that provides for loopback testing across circuit switched (e.g., TDM) and packet switched (e.g., ATM) boundaries would therefore be highly advantageous.

SUMMARY

A hybrid telecommunications component in accordance with the principles of the present invention affords loopback test capabilities across circuit/packet switched boundaries. In accordance with the principles of the invention a loopback test which encompasses at least a portion of the packet switched side of a hybrid system may be initiated from the circuit switched side of the hybrid device. Additionally, a loopback test which encompasses at least a portion of the circuit switched side of a hybrid system may be initiated from the packet switched side of the hybrid device. In an illustrative embodiment, when a loopback test of the circuit switched side is initiated by the packet switched side, the loopback test is carried out by the circuit switched side, with the results being reported by the circuit switched side to the packet switched side.

The cross-boundary loopback test capability is particularly useful in a device such as an extended 5ESS (or known as 7E), for example, which includes both packet switching facilities, in the form of a multi-service module (MSM or Packet Driver), and circuit switching facilities, in the form of the core switch. In such an application, the packet switched, circuit switched boundary would take the form of an asynchronous transfer mode (ATM)/ time division multiplexed (TDM) boundary. That is, the loopback testing would cross ATM/TDM boundaries, thereby providing for the isolation and repair of system failures in such a hybrid telecommunications component.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and further features, aspects, and advantages of the invention will be apparent to those skilled in the art from the following detailed description, taken together with the accompanying drawings in which:

Figure 1 is a conceptual block diagram of a hybrid telecommunications system in accordance with the principles of the present invention;

Figure 2 is a conceptual block diagram of a packet switching portion of a hybrid telecommunications system in accordance with the principles of the present invention;.

Figure 3 is a flow diagram which depicts the establishment of a loopback test across circuit and packet switched boundaries in accordance with the principles of the present invention and

Figure 4 is a conceptual block diagram that depicts the operation of a loopback test across circuit and packet switching boundaries in accordance with the principles of the present invention.

DETAILED DESCRIPTION

A hybrid telecommunications component in accordance with the principles of the present invention affords loopback test capabilities across circuit/packet switched boundaries. In accordance with the principles of the invention a loopback test which encompasses at least a portion of the packet switched side of a hybrid system may be initiated from the circuit switched side of the hybrid device. Additionally, a loopback test which encompasses at least a portion of the circuit switched side of a hybrid system may be initiated from the packet switched side of the hybrid device. In an illustrative embodiment, when a loopback test of the circuit switched side is initiated by the packet switched side, the loopback test is carried out by the circuit switched side, with the results being reported by the circuit switched side to the packet switched side.

The cross-boundary loopback test capability is particularly useful in a device such as an extended 5ESS, for example, which includes both packet switching facilities, in the form of a multi-service module (MSM), and circuit switching facilities, in the form of the core switch. In such an application, the packet switched, circuit switched boundary would take the form of an asynchronous transfer mode (ATM)/ time division multiplexed (TDM) boundary. That is, the loopback testing would cross ATM/TDM boundaries, thereby providing for the isolation and repair of system failures in such a hybrid telecommunications component.

In accordance with the principles of the present invention, a packet-switched/ circuit-switched hybrid device such as illustrated in the conceptual block diagram of Figure 1

includes a circuit switching section 102 and a packet switching section 104. The circuit switching section 102 communicates with the packet switching section 104 through a link 106 that may carry T1, E1, or STS1 data formats, or an internal format based on the above for example. The circuit switching section 102 communicates through an interface 108 with one or more other switches (not shown) via one or more trunks 110. The packet switching section 104 communicates through a packet switching gateway 113 with one or more other switches via one or more trunks 114. The packet switching gateway is a device that converts circuit switching information to packet switching and vice versa. The gateway's circuit switching side may be a loopback point to the circuit switching path and its packet switching side may be a loopback point to the packet switching path. In accordance with the principles of the invention, the circuit switched section 102 may initiate loopback tests which encompass one or more segments of the communications path provided by the packet switched side of the hybrid, including the link 106, the packet switching section 104, the trunk(s) 114, and the packet switching section's gateway 113.

ATM Loopback tests are known, and discussed, for example, in International Telecommunications Union (ITU) recommendation I.610 (11/95) pages 16 through 22 which are hereby incorporated by reference in their entirety. On the circuit switched side, there are several test calls to test connections between two circuit switched central offices. Such loopback tests may employ a test call such as test call 108, for example, to establish the loopback. Test call 108 is known and employed by conventional Central Office Switches if the switches on both ends of a circuit being tested are circuit switched.

In accordance with the principles of the present invention, the basic approach to testing a hybrid switch is to set up a call from the circuit switching components to the packet switching components and loopback the path at a packet switching component, using the ITU I.610 recommendations. Then, the circuit switching side of such a hybrid device may establish a loopback test, via a looparound trunk/path with a loopback point at the gateway 113, for example. The looparound trunk, a trunk that originates and terminates in the same central switch office, may be established through provisioning. That is, by provisioning the trunk to have an egress port within the central office and an ingress

108. Even if the ATM switch's ingress port 122 or egress port 114 does not include IP routing capability, a modified IP Ping protocol employed by the packet switching gateway 113 enables the use of an IP Ping to establish a loopback between the circuit switching interface 108 and the ATM switch ingress port 122, or between the circuit switching interface 108 and the ATM switch egress port 114.

In the illustrative block diagram of Figure 2, the packet switching gateway 113 within the packet switching device 104 is illustratively embodied as an ATM multiplexer 116. The ATM multiplexer communicates with the ATM switching core 118 through ingress port 122, and the ATM switch communicates with an ATM communications circuit through the egress port 114. The ATM multiplexer would typically communicate with the circuit switching device 102 via the link 106.

A loopback test may employ loopback on demand in such a system, as discussed in relation to the sequence diagram of Figure 3. In this figure, we use the Q.931 messages to describe the way to set up a path dynamically between device 102 and device 116. Alternatively, it may be advantageous to use the Internet Protocol Device Control (IPDC), rather than Q.931, to set up the connection. The IPDC can carry a message for device 102 to ask device 116 to set up a loopback point at device 118. This message can not be carried by the traditional Q.931 messages. However, since the IPDC implementation may vary depending on the individual implementor, a Q.931 message implementation is used to illustrate the concept. The loopback test, which crosses the circuit switching/packet switching boundary in accordance with the principles of the present invention, is illustratively initiated on the circuit switching side of a hybrid device, in circuit switching device 102, for example. The processing steps which take place between the circuit switching side and the ATM multiplexer may be carried out according to processes described in detail in CCITT Q.931 and the steps which take place between the ATM multiplexer and the ATM switch are carried out according to processes described in detail in CCITT Q.2931, which documents are hereby incorporated by reference in their entirety.

In step 300 the circuit switching device 102, which may be a 5ESS core, for example, sets up a loop around trunk by sending a request to the ATM multiplexer 116 for a

connection to the ATM switch 118. This loopback request message may be carried out using an IPDC message, but we use available Q.931 messages to illustrate the concept. However, the intent for the loopback and the designation of the loopback point are implemented using an IPDC message, or messages, not directly by Q.931. In step 302 the ATM multiplexer passes this request along to the ATM switch 118. In step 304 the ATM multiplexer returns a call proceeding message to the switching device 102. From step 304 the process proceeds to step 306 where the ATM switch establishes a channel, that is, allocates bandwidth, etc., between itself and the ATM multiplexer 116. In step 308 a similar channel is established between the ATM multiplexer and the switching device 102. After establishing the loopback connection, in step 310 a loopback test is performed. The step 310 consists of two substeps: (1) establish an ATM connection path, (2) use ITU I.610 standard to set up an ATM OAM lookback. In the second substep, the the ATM switch is designated as the loopback point. In the course of the loopback test, the circuit switching device 102 sending a test message and the ATM switch, which in this example receives the message at its ingress port 122 and sends a return message from its egress port 114, returns a loopback message to the circuit switching device 102. If the connection fails the test, a fault lies somewhere between the circuit switching device 102 and the ATM switch 118, inclusively. Accordingly, the circuit switching device, 102 will be aware of the failed path and will not send calls to that path. Additionally, the circuit switching device 102 may provide alarms that will initiate corrective measures.

After completion of the loopback test the circuit switching device 102 requests a disconnect in step 312. The ATM multiplexer 116 passes this disconnect request along to the ATM switch 118 in step 314. In step 316 the ATM switch releases the channel between itself and the ATM multiplexer 116 and, in step 318 the ATM multiplexer 116 releases the channel between itself and the circuit switching device 102.

In accordance with the principles of the present invention, the packet switching gateway 113 may be embodied as an IP router, as illustrated in the conceptual block diagram of Figure 4, wherein the packet switching device 104 includes an IP router 112 that communicates with the ATM switch 118 through the ingress port 122. In this example,

Sub
AI
Cmk

66T22T 49T22T20

the interwork unit, i.e. the packet switching gateway, is a modem pool device. The IP router 112 may take the form of a modem pool device, for example. In this illustrative embodiment, the circuit switching device 102, which may be a 5ESS core, for example, offers IP communications capability for communications with the packet switching gateway 113, which, in this embodiment, is a modem pool device. It is also assumed that the ATM switch 118 does not include IP routing capability, and that a path between the ATM switch and the switching gateway 113 (modem pool device) is established. The physical path between the modem pool device, 116, and the ATM switch, 118, can be done either through provisioning or through ATM signaling. Given these assumptions, the circuit switching device 102 may use a route index to identify which of its ports to employ in the loopback test. After determining which port to employ for the test, the circuit switching device 102 sends an IP packet to the switching gateway 113. The IP packet includes a special address that identifies the ATM egress port 114 to which the packet is to be addressed. That is, the source address within the IP datagram is used as the destination address, thereby creating a loopback. An incoming facility, x, is also employed to identify to the switching gateway 113 the address and channel number, y, of the ATM switch's egress port 113.

Upon receipt of the IP datagram identified as a loopback datagram, the IP router 112 swaps the source and destination IP addresses of the received datagram, thereby looping the datagram back to the source. If the datagram sent to the IP router 112 was an ICMP type 8 message, the router will return an ICMP type 0 response in order to satisfy the "Ping" requirements. Additionally, the IP router 112 will set up an entry in its routing table, an internal entry not included in neighborhood hello messages, that includes a facility address and channel number for a loopback. This routing message will eventually time out and be removed from the routing table. The received IP datagram may be converted to ATM cells or encapsulated as a frame relay packet set to the virtual path identifier/virtual channel identifier (VPI/VCI) or data link connection identifier (DLCI) that is connected to an ATM egress port which loops back everything it receives. Since the IP router 112 swaps source and destination addresses in the IP datagram, the datagram is routed to the

Sub
AI
Cmt

new routing entry (the source address) and the IP ping response (ICMP type 0) is returned to complete the loopback test.

The foregoing description of specific embodiments of the invention has been presented for the purposes of illustration and description. It is not intended to be exhaustive or to limit the invention to the precise forms disclosed, and many modifications and variations are possible in light of the above teachings. The embodiments were chosen and described to best explain the principles of the invention and its practical application, and to thereby enable others skilled in the art to best utilize the invention. It is intended that the scope of the invention be limited only by the claims appended hereto.

What is claimed is:

667327-1373460